

## THE ALON RESIDENCE

2256 DEODARA DR. LOS ALTOS, CALIFORNIA

### CONSULTANTS

DESIGN BY : KHADIY DESIGN 4657 TAMPICO WAY SAN JOSE, CA 95118 Phone (408) 888-6662 Email Address: INFO@KHADIVDESIGN.COM

CIVIL DRAWING DILIP KISHNANI, PE STERLING CONSULTANTS 46560 FREMONT BOULEVARD, SUITE 205 FREMONT, CA 94538 925-705-3633 CELL

### ZONING COMPLIANCE

	Existing	Proposed	Allowed/Required
LOT COVERAGE:  Land area covered by all structures that are over 6 feet in height	<b>1,832.16</b> square feet ( <b>16.1</b> _%)	2,761.99 quare feet ( 24.2_%)	3412.5 square feet (_30_%) TWO STORY
FLOOR AREA: Measured to the outside surfaces of exterior walls	1st Flr: <b>1709.16</b> sq ft 2 <sup>nd</sup> Flr: <b>699</b> sq ft <b>Total: 2,378.16</b> sq ft ( <b>20.9</b> %)	1st Flr: <u>2299.98</u> sq ft 2 <sup>nd</sup> Flr: <u>1579.73</u> sq ft Total: <u>3,879.71</u> sq ft ( <u>34.1</u> %)	3887.5 square feet (34.1%)
SETBACKS: Front Rear Right side (1st/2nd) Left side (1st/2nd)	25'-3" feet 53'-10" feet 19'-7" feet/59'-8"feet 23'-7" feet/23'-7'feet	25'-0" feet 25'-0" feet 13'-3" feet/40'-8'feet 23'-7" feet/23'-7'feet	25 feet 25 feet 10 feet/17.5feet 20 feet/17.5feet
HEIGHT:	21'-4"feet (+/-)	<b>24'-8"</b> feet	<b>27</b> feet


### SQUARE FOOTAGE BREAKDOWN

	Existing	Change in	Total Proposed
HABITABLE LIVING AREA: Includes habitable basement areas	1,890.66 square feet	<b>2,451.06</b> square feet	<b>4,341.72</b> square feet
NON- HABITABLE AREA:  Does not include covered porches or open  structures	487.5 square feet GARAGE	square feet	487.5 square feet GARAGE

### LOT CALCULATIONS

NET LOT AREA:	square feet
FRONT YARD HARDSC Hardscape area in the front yar	I I4UU somare teet (43 %)
LANDSCAPING BREAKDOWN:	Total hardscape area (existing and proposed):  Existing softscape (undisturbed) area:  New softscape (new or replaced landscaping) area:  Sum of all three should equal the site's net lot area  6053.5 sq ft  5,321.5 sq ft

## VICINITY MAP



## BUILDING CODE DATA

OCCUPANCY:

R-3 / U SINGLE FAMILY RESIDENCE WITH ATTACHED GARAGE. CONSTRUCTION TYPE:

FIRE SPRINKLER

BUILDING CODE:

ALL APPLICABLE CURRENT CODES TO THE COUNTY OF SANTA CLARA AND THE STATE OF CALIFORNIA 2019 CALIFORNIA BLD'G CODE (CBC)

2019 CALIFORNIA PLUMBING CODE (CPC) 2019 CALIFORNIA MECHANICAL CODE (CMC)

2019 CALIFORNIA ELECTRICAL CODE (CEC) 2019 CALIFORNIA GREEN BUILDING CODE (CALGREEN) 2019 CALIFORNIA RESIDENTIAL CODE

2019 CALIFORNIA ENERGY CODE

### PROJECT DESCRIPTION

ADDITION AND REMODEL TO EXISTING TWO STORY RESIDENCE

PROJECT ADDRESS:

2256 DEODARA DR. LOS ALTOS, CA

ZONING DISTRICT:

RI-10

## TABULATION

## F.A.R

THE MAXIMUM FLOOR AREA IS 3,850 SQUARE FEET PLUS 10% OF THE REMAINING LOT AREA.

LOT AREA = 11375 11375 - 11000 =375

F.A.R = 3850 + 37.5 =3,887.5 SQ. FT.

## LOT COVERAGE

 $11375 \times 30\% = 3412.5$ 

### SHEET INDEX.

COYER SHEET/ PLANNING DATA BLUEPRINT FOR CLEAN BAY CALGREEN MANDATORY CHECKLIST

### ARCHITECTURAL

<u>CIVIL</u>

EXISTING SITE PLAN PROPOSED SITE PLAN EXISTING AREA CALCULATION DIAGRAM PROPOSED AREA CALCULATION DIAGRAM NEIGHBORHOOD COMPATIBILITY WORKSHEET NEIGHBORHOOD COMPATIBILITY WORKSHEET EXISTING FIRST FLOOR PLAN / DEMO PLAN EXISTING SECOND FLOOR PLAN / DEMO PLAN PROPOSED FIRST FLOOR PLAN PROPOSED SECOND FLOOR PLAN EXISTING ROOF PLAN / DEMO PLAN PROPOSED ROOF PLAN EXISTING & PROPOSED FRONT ELEVATION EXISTING & PROPOSED RIGHT SIDE ELEVATION

> EXISTING AND DEMOLITION GRADING AND DRAINAGE PLAN

EXISTING & PROPOSED REAR ELEVATION

EXISTING & PROPOSED LEFT SIDE ELEVATION


## No. Date Description

### Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

### Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

12-07-20 Date:

Scale: N.T.S FK Drawn By:

Job No: 2020.11

Signature:

Sheet Title:

COVER SHEET PLANNING DATA

Sheet No.:

## Heavy Equipment Operation

Best Management Practices for the



### Best Management Practices for the

- Site supervisors General contractors

Home builders

Developers

### Storm water Pollution from Heavy Equipment on Construction Sites

equipment from the site as soon as possible

parts, or clean equipment. Use only water for

Cover exposed fifth wheel hitches and other oily

or greasy equipment during rain events.

Poorly maintained vehicles and heavy equipment that leak fuel, oil, antifreeze or other fluids on the construction site are commor sources of storm drain pollution. Prevent spill and leaks by isolating equipment from runof channels, and by watching for leaks and other maintenance problems. Remove construction

**Doing The Right Job** 

any onsite cleaning.

Site Planning and Preventive Vehicle

Doing the Job Right

- ☐ Maintain all vehicles and heavy equipment. spect frequently for and repair leaks. ☐ Never hose down "dirty" pavement or Perform major maintenance, repair jobs, and impermeable surfaces where fluids have vehicle and equipment washing off site where spilled. Use dry cleanup methods
- (absorbent materials, cat litter, and/or rags) whenever possible and properly ☐ If you must drain and replace motor oil, radiator dispose of absorbent materials. coolant, or other fluids on site, use drip pans or drop cloths to catch drips and spills. Collect all Sweep up spilled dry materials spent fluids, store in separate containers, and immediately. Never attempt to "wash
- properly dispose as hazardous waste (recycle them away" with water, or bury them. Use as little water as possible for dust ☐ Do not use diesel oil to lubricate equipment control. Ensure water used doesn't

Spill Cleanup

leave silt or discharge to storm drains. Clean up spills on dirt areas by digging up and properly disposing of

Clean up spills immediately when they

- Report significant spills to the appropriate local spill response
- agencies immediately. If the spill poses a significant hazard to human health and safety, property or

## Roadwork

Best Management Practices for the Construction Industry

the environment, you must also report it to the State Office of Emergency

## **Paving**



## Best Management Practices for the

### Driveway/sidewalk/parking lot construction Seal coat contractors

## Road crews

### · Operators of grading equipment, paving machines, dump trucks, concrete mixers Construction inspectors

 General contractors Home builders Developers

### Do not use diesel oil to lubricate equipment parts or clean equipment.

or when rain is forecast, to prevent fresh materials from contacting stormwater runoff. Cover and seal catch basins and manholes when applying seal coat, slurry seal, fog seal,

**During Construction** 

Protect drainage ways by using earth dikes sand bags, or other controls to divert or trap

whenever possible, or dispose of properly.

Avoid paving and seal coating in wet weather,

control plans for roadway embankments.

☐ Check for and repair leaking equipment.

### Storm Drain Pollution from Roadwork

Road paving, surfacing, and pavement removal happen right in the street, where there are numerous opportunities for asphalt, saw-cut slurry, or excavated material to illegally enter storm drains. Extra planning is required to store and dispose materials properly and guard against pollution of storm drains, creeks, and the Bay

**Doing The Job Right** 

### **Doing The Job Right** ☐ Never wash excess material from exposed- aggregate concrete or similar treatments into a street or storm drain **General Business Practices** Collect and recycle, or dispose to dirt Develop and implement erosion/sediment

- Cover stockpiles (asphalt, sand, etc.) ☐ Schedule excavation and grading work during and other construction materials with plastic tarps. Protect from rainfall and prevent runoff with temporary roofs or plastic sheets and berms.
- ☐ Perform major equipment repairs at designated Park paving machines over drip pans or areas in your maintenance yard, where absorbent material (cloth, rags, etc.) to cleanup is easier. Avoid performing equipment catch drips when not in use.
- repairs at construction sites. Clean up all spills and leaks using "dry" ☐ When refueling or when vehicle/equipment methods (with absorbent materials maintenance must be done on site, designate and/or rags), or dig up, remove, and a location away from storm drains and creeks.
- Collect and recycle or appropriately dispose of excess abrasive gravel or Recycle used oil, concrete, broken asphalt, etc.

properly dispose of contaminated soil

Avoid over-application by water trucks

### Asphalt/Concrete Removal

- Avoid creating excess dust when breaking asphalt or concrete. After breaking up old pavement, be sure to remove all chunks and pieces. Make
  - sure broken pavement does not come in contact with rainfall or runoff. ☐ When making saw cuts, use as little water as possible. Shovel or vacuum saw-cut slurry and remove from the site.
  - Cover or protect storm drain inlets during saw-cutting. Sweep up, and properly dispose of, all residues. Sweep, never hose down streets to clean up tracked dirt. Use a street sweeper or vacuum truck. Do not dump

vacuumed liquor in storm drains.

☐ Never clean brushes or rinse paint

drain, French drain, or stream,

For water-based paints, paint out

containers into a street, gutter, storm

brushes to the extent possible, and rinse

into a drain that goes to the sanitary

sewer. Never pour paint down a storm

For oil-based paints, paint out brushes to

the extent possible and clean with thinner

reuse thinners and solvents. Dispose of

excess liquids and residue as hazardous

Paint chips and dust from non-hazardous

and disposed of as trash.

state-certified contractor.

dry stripping and sand blasting may be

Chemical paint stripping residue and chips

and dust from marine paints or paints

containing lead, mercury or tributyl tin

Lead based paint removal requires a

exteriors with high-pressure water, block

storm drains. Direct wash water onto a di

area and spade into soil. Or, check with

find out if you can collect (mop or vacuum)

building cleaning water and dispose to the

sanitary sewer. Sampling of the water may

be required to assist the wastewater

treatment authority in making its decision.

must be disposed of as hazardous wastes.

swept up or collected in plastic drop cloths

or solvent in a proper container. Filter and

Painting Cleanup

Paint Removal

### Patio construction workers Construction inspectors

- General contractors Home builders
- Developers Concrete delivery/pumping workers

Masons and bricklayers

Sidewalk construction crews

**Fresh Concrete** 

Best Management Practices for the

Best Management Practices for the

and Mortar

**Application** 

Construction Industry

### **Doing The Job Right** General Business Practices

☐ Wash out concrete mixers only in designated wash-out areas in your yard, away from storm drains and waterways, where the water will flow into a temporary waste pit in a dirt area. Let water percolate through soil and dispose of settled, hardened concrete as garbage. Whenever possible, recycle washout by pumping back into mixers for reuse.

- ☐ Wash out chutes onto dirt areas at site that do not flow to streets or drains
- Always store both dry and wet materials under cover, protected from rainfall and runoff and away from storm drains or waterways. Protect dry materials from wind. ☐ Secure bags of cement after they are open. Be

sure to keep wind-blown cement powder away

from streets, gutters, storm drains, rainfall, and

☐ Do not use diesel fuel as a lubricant on concrete forms, tools, or trailers.

### Storm Drain Pollution from Fresh Concrete and Mortar Applications

Fresh concrete and cement-related mortars that wash into lakes, streams, or estuaries are toxic to fish and the aquatic environment. Disposing of these materials to the storm drains or creeks can block storm drains, causes serious problems, and is

### **During Construction**

Don't mix up more fresh concrete or cement than you will use in a two-hour

- ☐ Set up and operate small mixers on tarps or heavy plastic drop cloths. ☐ When cleaning up after driveway or
  - dirt areas, not down the driveway or into the street or storm drain. Protect applications of fresh concrete

sidewalk construction, wash fines onto

and mortar from rainfall and runoff until

- Wash down exposed aggregate concrete only when the wash water can 1) flow onto a dirt area; (2) drain onto a permed surface from which it can be pumped and disposed of properly; or (3 be vacuumed from a catchment created by blocking a storm drain inlet. If necessary, divert runoff with temporary berms. Make sure runoff does not reac
- ☐ When breaking up pavement, be sure to pick up all the pieces and dispose of properly. Recycle large chunks of proken concrete at a landfill.
- ☐ Never bury waste material. Dispose of small amounts of excess dry concrete, grout, and mortar in the trash.

gutters or storm drains.

■ Never dispose of washout into the street, storm drains, drainage ditches, or

## **Preventing Pollution:** It's Up to Us

In the Santa Clara Valley, storm drains

and fight storm water pollution. TO

Spill Response Agencies

State Office of Emergency Services Warning

Local Pollution Control

Agencies

County of Santa Clara Pollution Prevention

County of Santa Clara Integrated Waste

County of Santa Clara District Attorney

Environmental Crimes Hotline:

Santa Clara County

Santa Clara Valley Water

Recycling Hotline:

Control Plant:

Building Department:

Management Program: (408) 441-1198

Santa Clara Valley Water District Pollution

Regional Water Quality Control Board San

Altos Hills, Mountain View, Palo Alto, Stanford

Palo Alto Regional Water Quality

Francisco Bay Region: (510) 622-2300

Serving East Palo Alto Sanitary District, Los Altos, Los

City of Los Altos

Engineering Department: (650) 947-2780

Santa Clara County Environmental Health

800-852-7550

(408) 299-6930

(408) 441-1195

(408) 299-TIPS

1-800-533-8414

(408) 265-2600

1-888-510-5151

(650) 329-2598

(650) 947-2752

this drawing sheet.

Center (24 hours):

DIAL 9-1-1

Services:

transport water directly to local creeks and San Francisco Bay without treatment. Storm water pollution is a serious problem for wildlife dependent on our waterways and for the people who live near polluted streams or bay lands. Some common sources of this pollution include spilled oil, fuel, and fluids from vehicles and heavy equipment; construction debris; sediment created by erosion; landscaping runoff containing pesticides or weed killers; and materials such as used motor oil, antifreeze, and paint products that people pour or spill into a street or storm drain. Thirteen valley municipalities have joined together with Santa Clara County and the Santa Clara Valley Water District to educate local residents and businesses

### Project: comply with this program, contractors most comply with the practices described

Mr. and Mrs. Alon

Client:

2256 DEODARA DR. LOS ALTOS, CA

No. Date Description

THE USE OF THESE PLANS AND SPECIFICATION SHALL

BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH

THEY WERE PREPARED AND PUBLICATION THEREOF

SHALL BE EXPRESSLY LIMITED TO SUCH USE REUSE

REPRODUCTION OR PUBLICATION BY ANY METHOD.

IN WHOLE OR IN PART IS PROHIBITED: TITLE TO THE

CONTACT WITH THESE PLANS AND SPECIFICATIONS

SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE

Mr. and Mrs. Alon


2256 DEODARA DR.

LOS ALTOS, CA

PLANS AND SPECIFICATIONS REMAINS WITH

ACCEPTANCE OF THE RESTRICTIONS.

KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662

farnaz@khadivdesign.com

## KHADIV-DESIGN

12-07-20 Date:

Scale: N.T.S

Drawn By:

Job No: 2020.11

FK

Sheet Title:

FOR A CLEAN BAY

Sheet No.:

## Gardening, and

Construction Industry



- Gardeners Swimming pool/spa service and repair
- Home builders Developers

Homeowners

### **Best Management Practices for the**

### **General Business Practices** Protect stockpiles and landscaping materials

- from wind and rain by storing them under tarps Store pesticides, fertilizers, and other chemicals indoors or in a shed or storage
- Schedule grading and excavation projects during dry weather.
- Use temporary check dams or ditches to divert runoff away from storm drains. Protect storm drains with sandbags or other
- Re-vegetation is an excellent form of erosion control for any site Landscaping/Garden Maintenance Use pesticides sparingly, according to instructions on the label. Rinse empty containers, and use rinse water as product
- Dispose of rinsed, empty containers in the rash. Dispose of unused pesticides as Collect lawn and garden clippings, pruning
- waste, and tree trimmings. Chip if necessary ☐ In communities with curbside pick-up of yard waste, place clippings and pruning waste at the curb in approved bags or containers. Or, take to a landfill that composts vard waste. No

### commercial properties Storm Drain Pollution

From Landscaping and Swimming Pool Maintenance Many landscaping activities expose soils and increase the likelihood that earth and garden chemicals will run off into the storm drains during irrigation or when it rains. Swimming pool water

### dirt shoulders, unless you are piling them for recycling (allowed by San Jose and unincorporated County only). Sweep up any leaves, litter or residue in gutters or on In San Jose, leave yard waste for curbside

recycling pickup in piles in the street. 18 inches from the curb and completely out of the flow line to any storm drain. Pool/Fountain/Spa Maintenance

Do not use copper-based algaecides.

Control algae with chlorine or other

alternatives, such as sodium bromide.

Do not blow or rake leaves, etc. into the

street, or place yard waste in gutters or on

**Draining Pools Or Spas** When it's time to drain a pool, spa, or fountain, please be sure to call your local wastewater treatment plant before you start for further quidance on flow rate restrictions, backflow prevention, and handling special cleaning

- waste (such as acid wash). Discharge flow shall not exceed 100 gallon per minute. Never discharge pool or spa water to a street or storm drain; discharge to a
- sanitary sewer cleanout. If possible, when emptying a pool or spa, then recycle/reuse water by draining it gradually onto a landscaped area

### curbside pickup of vard waste is available for

- Filter Cleaning Never clean a filter in the street or near a storm drain. Rinse cartridge and diatomaceous earth filters onto a dirt area and spade filter residue into soil. Dispose
- of spent diatomaceous earth in the If there is no suitable dirt area, call your instructions on discharging filter backwash containing chlorine and copper-based algaecides or rinse water to the sanitary sewer.

## Painting and **Application of** Solvents and

Construction Industry



## Best Management Practices for the

- - Paperhangers
  - Graphic artists Dry wall crews Floor covering installers

Home builders

Developers

**Adhesives** Best Management Practices for the



- General contractors

### **Handling Paint Products** ☐ Keep all liquid paint products and wastes away from the gutter, street, and storm drains. Liquid residues from paints, thinners solvents, glues, and cleaning fluids are hazardous wastes and must be disposed of at a hazardous waste collection facility (contact your local stormwater program listed on the back of this brochure)

☐ When thoroughly dry, empty paint cans, used

brushes, rags, and drop cloths may be

- disposed of as garbage in a sanitary landfill. Empty, dry paint cans also may be recycled as ☐ Wash water from painted buildings constructed before 1978 can contain high amounts of lead, even if paint chips are not present. Before you begin stripping paint or cleaning pre-1978 building exteriors with water under high
- scrapings to a local laboratory. See Yellow Pages for a state-certified laboratory. ☐ If there is loose paint on the building, or if the paint tests positive for lead, block storm drains. letermine whether you may discharge water to

All paints, solvents, and adhesives contain chemicals that are harmful to wildlife in local Toxic chemicals may come from liquid or solid products or from cleaning residues or rags. Pain should be recycled when possible, or disposed of properly to prevent these materials from flowing into storm drains and watercourses.

Doing The Job Right

General Business Practices

## pressure, test paint for lead by taking pain

the sanitary sewer, or if you must send it offsite for disposal as hazardous waste. Storm Drain Pollution from Paints, Solvents, and Adhesives

creeks. San Francisco Bay, and the Pacific Ocean material and wastes, adhesives and cleaning fluids

Schedule excavation and grading work during

Perform major equipment repairs away from the

maintenance must be done on site, designate a

☐ When refueling or vehicle/equipment

location away from storm drains.

**Practices During Construction** 

Do not use diesel oil to lubricate equipment

Remove existing vegetation only when

absolutely necessary. Plant temporary

vegetation for erosion control on slopes or

Protect down slope drainage courses, streams,

and storm drains with wattles, or temporary

drainage swales. Use check dams or ditches

to divert runoff around excavations. Refer to

where construction is not immediately planned.

### Whenever Possible Recycle or donate excess water-based (latex) paint, or return to supplier. Reuse leftover oil-based paint. Dispose

of non-recyclable thinners, sludge and unwanted paint, as hazardous waste. Unopened cans of paint may be able to be returned to the paint vendor. Check with the vendor regarding its "buy-back" policy

Recycle/Reuse Leftover Paints

## Cover stockpiles and excavated soil with

- 1. Check for Toxic Pollutants Check for odors, discoloration, or an oily sheen on groundwater.
- If contamination is suspected, have the water tested by a certified laboratory. Depending on the test results, you may b allowed to discharge pumped groundwate to the storm drain (if no sediments present) or sanitary sewer. OR, you may be required to collect and haul pumped
- Check for Sediment Levels If the water is clear, the pumping time is less than 24 hours, and the flow rate is less than 20 gallons per minute, you ma pump water to the street or storm drain If the pumping time is more than 24 hours
- and the flow rate greater than 20 gpm, If the water is not clear, solids must be filtered or settled out by pumping to a settling tank prior to discharge. Options for filtering include: Pumping through a perforated pipe sunk part way into a small pit filled
- Pumping from a bucket placed below water level using a submersible pump; Pumping through a filtering device such as a swimming pool filter or filter fabric wrapped around end of suction

## secured tarps or plastic sheeting. **Dewatering Operations**

- agency and ask whether the groundwater
- groundwater offsite for treatment and disposal at an appropriate treatment
- call your local wastewater treatment plant

## ☐ Call your local wastewater treatment

pump water through a grassy swale prior


# Blueprint for a Clean Bay

responsibility for the activities that occur on a construction site You may be held responsible for any environmental damage caused by your subcontractors or employees.

## **Best Management Practices for the Construction Industry**



**Urban Runoff Pollution Preventio** 



ram	DESIGNED BY: LARRY LIND	APPROVED BY:
am	DRAWN BY: VICTOR CHEN	CITY ENGINEE
	CHECKED BY: JIM GUSTAFSON	SHEET

	DESIGN
on Program	LARRY
on rogium	DRAWN VICTOR
	CHECK

CITY OF LOS ALTOS OCTOBER, 2003 SCALE: N.T.S. R.C.E. DRAWING NO: SHEETS

## **Pool Maintenance** Best Management Practices for the

- General contractors

## Construction **And Site**

## Best Management Practices

For Construction

**Best Management Practices for the** 

### General contractors Site supervisors Inspectors

Construction sites are common sources of storm water pollution. Materials and wastes that blow or wash into a storm drain, gutter, or street have a direct impact on local creeks and the Bay. As a contractor, or site supervisor, owner or operator of a site, you may be responsible fo any environmental damage caused by your

subcontractors or employees

- nousekeeping practices are used.
- Control the amount of runoff crossing your site (especially during excavation!) by using berms or temporary or permanent drainage ditches to divert water flow around the site. Reduce storm water runoff velocities by constructing temporary check dams or berms where appropriate. Train your employees and subcontractors. Make these best management practices

erosion controls before rain begins. Use the

Erosion and Sediment Control Manual, available

from the Regional Water Quality Control Board,

- Good Housekeeping Practices Designate one area of the site for auto parking, vehicle refueling, and routine equipment maintenance. The designated area should be well away from streams or storm drain inlets.
- contamination at the source. Cover exposed piles of soil or construction materials with plastic sheeting or temporary roofs. Before it rains. sweep and remove materials from surfaces that drain to storm drains, creeks, or channels. Keep pollutants off exposed surfaces.

Place trashcans and recycling receptacles

Doing The Job Right

chemicals are toxic to aquatic life.

Keep an orderly site and ensure good Maintain equipment properly.

Cover materials when they are not in use.

- and drainage channels ☐ Ensure dust control water doesn't leave site or discharge to storm drains Advance Planning To Prevent Pollution ☐ Schedule excavation and grading activities for dry weather periods. To reduce soil erosion.
- available to everyone who works on the
- bermed if necessary. Make major repairs off
- ☐ In addition to local building permits, you Keep materials out of the rain – prevent runoff will need to obtain coverage under the State's General Construction Activity

- Clean up leaks, drips and other spills immediately so they do not contaminate soil or groundwater or leave residue on paved surfaces. Use dry cleanup methods whenever possible. If you must use water, use just enough to keep the dust down.
- frequently for leaks. Place dumpsters unde roofs or cover with tarps or plastic sheeting secured around the outside of the dumpster. Never clean out a dumpster by hosing it down on the construction site.
- Materials/Waste Handling □ Practice Source Reduction -- minimize waste when you order materials. Order only the amount you need to finish the job. Use recyclable materials whenever possible. Arrange for pick-up of recyclable
- antifreeze, batteries, and tires. Dispose of all wastes properly. Many construction materials and wastes including solvents, water-based paints, vehicle fluids, broken asphalt and concrete recycled. Materials that cannot be recycled must be taken to an appropriate landfill or

# Cover and maintain dumpsters. Check

- Set portable toilets away from storm drains. Make sure portable toilets are in good working order. Check frequently for leaks.
- materials such as concrete, asphalt, scrap metal, solvents, degreasers, cleared vegetation, paper, rock, and vehicle maintenance materials such as used oil
- disposed of as hazardous waste. Never bury waste materials or leave them in the street or near a creek or stream bed.

Storm water Permit if your construction

site disturbs one acre or more. Obtain

information from the Regional Water

Quality Control Board.

## Bulldozer, back hoe, and grading machine

 Dump truck drivers Site supervisors General contractors

Developers

### the Regional Water Quality Control Board's Erosion and Sediment Control Field Manual for proper erosion and sediment control Storm Drain Pollution

destroy habitats in creeks and the Bay. Effective erosion control practices reduce the amount of runoff crossing a site and slow the flow with check dams or roughened ground surfaces. Contaminated groundwater is a common problem in

without treatment is prohibited.

### from Earth-Moving Activities and Dewatering Soil excavation and grading operations loosen large amounts of soil that can flow or blow into storm drains when handled improperly. Sediments in runof can clog storm drains, smother aquatic life, and

dewatering site into any water of the state

the Santa Clara Valley. Depending on soil types and site history, groundwater pumped from construction sites may be contaminated with toxics (such as oil or solvents) or laden with sediments. Any of these When discharging to a storm drain, protect pollutants can harm wildlife in creeks or the Bay, or the inlet using a barrier of burlap bags interfere with wastewater treatment plant operation. filled with drain rock, or cover inlet with filter fabric anchored under the grate. OR Discharging sediment-laden water from a

### Los Altos Municipal Code Chapter 10.08.390 Non-storm water discharges

Los Altos Municipal Code Section 10.08.430 Requirements for construction operations.

Criminal and judicial penalties can be assessed for non-compliance.

Unlawful discharges. It shall be unlawful to discharge any domestic waste or industrial waste into storm drains, gutters, creeks, or San Francisco Bay. Unlawful discharges to storm drains shall include, but not be limited to, discharge from toilets; sinks; industrial processes; cooling systems; boilers; fabric cleaning; equipment cleaning; vehicle cleaning; construction activities, including, but not limited to, painting, paving, concrete placement, saw cutting and grading; swimming pools; spas; and fountains, unless specifically

Los Altos Municipal Code Requirements

- permitted by a discharge permit or unless exempted pursuant to guidelines published by the superintendent. Threatened discharges. It shall be unlawful to cause hazardous materials, domestic waste, or industrial waste to be deposited in such a manner or location as to constitute a threatened discharge into storm drains, gutters, creeks or San Francisco Bay. A "threatened discharge" is a condition creating a substantial probability of harm, when the probability and potential extent of harm make it reasonably necessary to take immediate action to prevent, reduce or mitigate damages to persons, property or natural resources. Domestic or industrial wastes that are no longer contained in a pipe, tank or other container are considered to be threatened discharges unless they are actively being cleaned up.
- available at the construction sites for all projects where the proposed construction site is equal to or greater than one acre of disturbed soil and for any other projects for which the city engineer determines is necessary to protect surface waters. Preparation of the plan shall be in accordance with guidelines published by the city engineer A storm water pollution prevention plan shall be prepared and available at the construction sites for all projects greater than one acre of disturbed soil and for any other projects for which the city engineer determines that a storm water management plan is necessary to protect surface waters. Preparation of the plan shall be in accordance with guidelines published by the city engineer. Prior approval shall be obtained from the city engineer or designee to discharge water pumped from construction sites to the storm drain. The city engineer or designee may require gravity settling and filtration upon a determination that either or both would

A spill response plan for hazardous waste, hazardous materials and uncontained construction materials shall be prepared and

improve the water quality of the discharge. Contaminated groundwater or water that exceeds state or federal requirements for

discharge to navigable waters may not be discharged to the storm drain. Such water may be discharged to the sewer, provide

that the requirements of Section 10.08.240 are met and the approval of the superintendent is obtained prior to discharge. No cleanup of construction debris from the streets shall result in the discharge of water to the storm drain system; nor shall any construction debris be deposited or allowed to be deposited in the storm drain system. (Prior code § 5-5.643)

# Remember: The property owner and the contractor share ultimate

Santa Clara

Signature:

**BLUEPRINT** 

# Construction Industry

## Vehicle and equipment operators

## Landscaping,



- Landscapers

# General

## Supervision

 Home builders Developers Storm Drain Pollution from Construction Activities

should never be discharged to storm drains. These

- ☐ Keep materials away from streets, storm drains plant temporary vegetation or place other
- construction site. Inform subcontractors about the storm water requirements and their own

# And

## **Activities**

Construction Industry

## **Earth-Moving** Dewatering

Best Management Practices for the

## **Best Management Practices for the**

## Home builders





### 2019 CALGREEN RESIDENTIAL CHECKLIST **MANDATORY ITEMS - Version 1.01.20**

COMMUNITY DEVELOPMENT DEPARTMENT – BUILDING DIVISION KIRK BALLARD, BUILDING OFFICIAL ONE NORTH SAN ANTONIO ROAD • LOS ALTOS, CA 94022-3088 (650) 947-2752 ● FAX/EMAIL- BUILDING@LOSALTOSCA.GOV ● WWW.LOSALTOSCA.GOV

### **PURPOSE**:

The 2019 CALGreen Code applies to all newly constructed hotels, motels, lodging houses, dwellings, dormitories, condominiums, shelters, congregate residences, employee housing, factory-built housing and other types of dwellings with sleeping accommodations and new accessory buildings associated with such uses. This section also applies to additions and alterations where there is an increase in conditioned space and specifies that these requirements only apply to the specific area of the addition or alteration. Existing site and landscaping improvements that are not otherwise disturbed are not subject to the requirements of CALGreen.

Project Name:	ALON RESIDENCE
Project Address:	2256 DEODARA Dr.
Project Description:	ADDITION AND REMODEL TO EXISTING TWO STORY HOUSE

### Instructions (for projects of 300 sq. ft. or more):

**Environmental Comfort** 

3 Manual S-2014 or equivalent.

installation of HVAC systems.

or equivalent.

they are inspecting.

Verifications

4.507.2 Duct systems are sized, designed, and

equipment is selected using the following methods:

 Establish heat loss and heat gain values according to ANSI/ ACCA 2 Manual J-2016 or equivalent.

2. Size duct systems according to ANSI/ACCA 1 Manual D-2016

3. Select heating and cooling equipment according to ANSI/ACCA

**702.1** HVAC system installers are trained and certified in the proper

**702.2** Special inspectors employed by the enforcing agency must be qualified and able to demonstrate competence in the discipline

**703.1** Verification of compliance with this code may include construction documents, plans, specifications builder or installer certification, inspection reports, or other methods acceptable to the

enforcing agency which show substantial conformance.

**Installer and Special Inspector Qualifications** 

- 1. The owner or owner's agent shall employ a licensed qualified green-point rater (www.builditgreen.org) experienced with the 2019 California Green Building Standards Codes to verify and assure that all required work described herein is properly planned and implemented in the project.
- 2. The green-point rater, in collaboration with the design professional shall review Column 2 of this checklist, and initial all applicable measures, sign and date **Section 1 –Design Verification** at the end of this checklist., prior to submittal. Applicant to include these pages into the construction plans as well as provide (2) separate 8-1/2" x 11" signed copies.
- PRIOR TO FINAL INSPECTION BY THE BUILDING DEPARTMENT, the Green-Point Rater shall complete Column 3 and sign and Date Section 2 - Implementation Verification at the end of this checklist and submit the completed form to the Building Department.

	COLUMN 2	COLUMN 3
MANDATORY FEATURE OR MEASURE	Project	Verification
	Requirements Rater to initial applicable measures prior to submitting forms	Rater to verify during construction as applicable to project
Planning and Design –		
Site Development		
<b>4.106.2</b> A plan is developed and implemented to manage storm water drainage during construction		
<b>4.106.3</b> Construction plans shall indicate how site grading or a drainage system will manage all surface water flows to keep water from entering buildings.		
<b>4.106.4</b> Provide capability for electric vehicle charging for one- and two-family dwellings: townhouses with attached private garages; multifamily dwellings; and hotels/motels in accordance with Section 4.106.4.1, 4.106.4.2 or 4.106.4.3 as applicable.		

Energy Efficiency –	
<b>General 4.201.1</b> Building meets or exceeds the requirements of the California Building Energy Efficiency Standards <sup>3</sup> .	
Water Efficiency and Conservation – Indoor Water Use	
<b>4.303.1.</b> Plumbing fixtures (water closets and urinals) and fittings	
(faucets and showerheads) installed in residential buildings shall comply with the prescriptive requirements of Sections 4.303.1.1 through 4.303.1.4.4.	
<b>4.303.2</b> Plumbing fixtures and fittings required in Section 4.303.1 shall be installed in accordance with the <i>California Plumbing Code</i> , and shall meet the applicable referenced standards.	
<b>4.303.1.4.3</b> Metering faucets in residential buildings shall not deliver more than 0.2 gallons per cycle.	
Outdoor Water Use	
<b>4.304.1</b> Residential developments shall comply with a local water efficient landscape ordinance or the current California Department of Water Resources' Model Water Efficient Landscape Ordinance (MWELO), whichever is more stringent.	
Material Conservation and Resource Enhanced Durability and Reduced Maintenance	_
<b>4.406.1</b> Annular spaces around pipes, electric cables, conduits or other openings in plates at exterior walls shall be protected against the passage of rodents by closing such openings with cement mortar, concrete masonry or similar method acceptable to the enforcing agency.	
Construction Waste Reduction, Disposal and Re	ecvclina
<ul> <li>4.408.1 Recycle and/or salvage for reuse a minimum of 65 percent of the nonhazardous construction and demolition waste in accordance with one of the following:</li> <li>1. Comply with a more stringent local construction and demolition waste management ordinance; or</li> <li>2. A construction waste management plan per Section 4.408.2; or</li> <li>3. A waste management company per Section 4.408.3; or</li> <li>4. The waste stream reduction alternative per Section 4.408.4.</li> </ul>	
Building Maintenance and Operation	
<b>4.410.1</b> An operation and maintenance manual shall be provided to the building occupant or owner.	
<b>4.410.2</b> Where 5 or more multifamily dwelling units are constructed on a building site, provide readily accessible areas that serve the entire building and are identified for the depositing, storage and collection of non-hazardous materials for recycling, including (at a minimum) paper, corrugated cardboard, glass, plastics, organic waste, and metals or meet a lawfully enacted local recycling	

specified in Section 101.7	
Required prerequisite for this Tier.	
3. These measures are currently required elsewhere in statute or in regulation	

1. Green building measures listed in this table may be mandatory if adopted by a city, county, or city and county as

Address:2256 DEODARA Dr.  Description: ADDITION AND REMODEL TO EXISTING TWO STORY HOUSE  BIGN VERIFICATION  - "Design Verification" and SUBMIT THE ENTIRE CHECKLIST (COLUMNS 2 AND 3)  DING PERMIT APPLICATION TO THE BUILDING DEPARTMENT.  sible for compliance with CalGreen Standards has reviewed the plans and certifies that breby incorporated into the project plans and will be implemented into the project in its set forth in the 2019 California Green Building Standards Code as adopted by the dease Print)  Certified ICC CalGreen Special Inspector/Consulting Date	A A A A		N SIGNATURE DECLARATIONS	
Description: ADDITION AND REMODEL TO EXISTING TWO STORY HOUSE  BIGN VERIFICATION  - "Design Verification" and SUBMIT THE ENTIRE CHECKLIST (COLUMNS 2 AND 3) bing PERMIT APPLICATION TO THE BUILDING DEPARTMENT.  Sible for compliance with CalGreen Standards has reviewed the plans and certifies that reeby incorporated into the project plans and will be implemented into the project in its set forth in the 2019 California Green Building Standards Code as adopted by the dease Print)  Certified ICC CalGreen Special Inspector/Consulting  Date  Decetor (Please Print)  Phone No.  License No.	1250000	Project Name:ALON RESIDENCE		
SIGN VERIFICATION  "Design Verification" and SUBMIT THE ENTIRE CHECKLIST (COLUMNS 2 AND 3) DING PERMIT APPLICATION TO THE BUILDING DEPARTMENT.  Sible for compliance with CalGreen Standards has reviewed the plans and certifies that breby incorporated into the project plans and will be implemented into the project in its set forth in the 2019 California Green Building Standards Code as adopted by the dease Print)  Certified ICC CalGreen Special Inspector/Consulting  Date  Deceptor (Please Print)  Phone No.  License No.	MORNED DECEMBER	Project Address: 2256 DEODARA Dr.		
Date  Certified ICC CalGreen Special Inspector/Consulting  Date  Decetor (Please Print)  Decetor (Please Print)  Ding PERMIT APPLICATION TO THE BUILDING DEPARTMENT.  Ding PERMIT APPLICATION TO THE BUILDING DEPARTMENT.  Sible for compliance with CalGreen Standards has reviewed the plans and certifies that reby incorporated into the project plans and will be implemented into the project in the set forth in the 2019 California Green Building Standards Code as adopted by the decetor (Please Print)  Date  Decetor (Please Print)  License No.		Project Description: ADDITION AND REMODEL TO EXI	STING TWO STORY HOUS	
Pease Print)  Certified ICC CalGreen Special Inspector/Consulting  Date  Dector (Please Print)  Phone No.  License No.	Complete all lines o WITH THE PLANS  The design professi the items checked a accordance with the	AND BUILDING PERMIT APPLICATION TO THE BUILDING DEPA onal responsible for compliance with CalGreen Standards has review above are hereby incorporated into the project plans and will be implein	RTMENT.  ed the plans and certifies that mented into the project in	
Certified ICC CalGreen Special Inspector/Consulting Date Dector (Please Print) Phone No. License No.	City of Los Altos.  Design Professiona	's Signature	 Date	
Certified ICC CalGreen Special Inspector/Consulting  Date  Dector (Please Print)  Phone No.  License No.	9		2.00	
Pector (Please Print)  Phone No.  License No.	Design Professiona	's Name (Please Print)		
License No.	Signature of Green Group	Point Rater/Certified ICC CalGreen Special Inspector/Consulting	Date	
	Name of Green Poi	nt Rater/Inspector (Please Print)	Phone No.	
I EMENTATION VEDICATION	Email Address		License No.	
completed checklist, including column 3, together with all original signatures		nt Rater/Inspector (Please Print)		

was constructed in accordance with this Green Building Checklist and in accordance with the requirements of the

Date

Phone No.

License No.

**2019 California Green Building Standards Code** as adopted by the City of Los Altos.

Signature of Licensed Green Point Rater/Certified ICC CalGreen Special Inspector/

Consulting Group

Email address

Name of Green Point Rater/Inspector (Please Print)

Fireplaces	
4.503.1 Any installed gas fireplace shall be a direct-vent sealed-	
combustion type. Any installed woodstove or pellet stove shall	
comply with US EPA New Source Performance Standards (NSPS)	
emission limits as applicable, and shall have a permanent label	
indicating they are certified to meet the emission limits.	
Woodstoves, pellet stoves and fireplaces shall also comply with	
applicable local ordinances.	
Pollutant Control	
<b>4.504.1</b> Duct openings and other related air distribution component	
openings shall be covered during construction.	
<b>4.504.2.1</b> Adhesives, sealants and caulks shall be compliant with	
VOC and other toxic compound limits.	
<b>4.504.2.2</b> Paints, stains and other coatings shall be compliant with	
VOC limits.	
4.504.2.3 Aerosol paints and coatings shall be compliant with	
product weighted MIR limits for ROC and other toxic compounds.	
<b>4.504.2.4</b> Documentation shall be provided to verify that compliant	
VOC limit finish materials have been used.	
<b>4.504.3</b> Carpet and carpet systems shall be compliant with VOC	
limits.	
<b>4.504.4</b> 80 percent of floor area receiving resilient flooring shall	
comply with specified VOC criteria.	
4.504.5 Particleboard, medium density fiberboard (MDF) and	
hardwood plywood used in interior finish systems shall comply with	
low formaldehyde emission standards.	
Interior Moisture Control	_
<b>4.505.2</b> Vapor retarder and capillary break is installed at slab-on-	
grade foundations.	
4.505.3 Moisture content of building materials used in wall and floor	
framing is checked before enclosure.	
	'
Indoor Air Quality and Exhaust	
<b>4506.1</b> Each bathroom shall be provided with the following:	
1. ENERGY STAR fans ducted to terminate outside of the building.	
2. Fans must be controlled by a humidity control (separate or built-	
in); OR functioning as a component of a whole-house ventilation	
system.	
3. Humidity controls with manual or automatic means of adjustment,	
capable of adjustment between a relative humidity range of ≤ 50	
percent to a maximum of 80 percent	1

<b>ENVIRONMENTAL QUALITY</b>	
Fireplaces	
4.503.1 Any installed gas fireplace shall be a direct-vent sealed-combustion type. Any installed woodstove or pellet stove shall comply with US EPA New Source Performance Standards (NSPS) emission limits as applicable, and shall have a permanent label indicating they are certified to meet the emission limits. Woodstoves, pellet stoves and fireplaces shall also comply with applicable local ordinances.	
Pollutant Control  4.504.1 Duct openings and other related air distribution component openings shall be covered during construction.	
<b>4.504.2.1</b> Adhesives, sealants and caulks shall be compliant with VOC and other toxic compound limits.	
<b>4.504.2.2</b> Paints, stains and other coatings shall be compliant with VOC limits.	
<b>4.504.2.3</b> Aerosol paints and coatings shall be compliant with product weighted MIR limits for ROC and other toxic compounds.	
<b>4.504.2.4</b> Documentation shall be provided to verify that compliant VOC limit finish materials have been used.	
<b>4.504.3</b> Carpet and carpet systems shall be compliant with VOC limits.	
<b>4.504.4</b> 80 percent of floor area receiving resilient flooring shall comply with specified VOC criteria.	
<b>4.504.5</b> Particleboard, medium density fiberboard (MDF) and hardwood plywood used in interior finish systems shall comply with low formaldehyde emission standards.	
Interior Moisture Control	
<b>4.505.2</b> Vapor retarder and capillary break is installed at slab-on-grade foundations.	
<b>4.505.3</b> Moisture content of building materials used in wall and floor framing is checked before enclosure.	
Indoor Air Quality and Exhaust	
4506.1 Each bathroom shall be provided with the following:  1. ENERGY STAR fans ducted to terminate outside of the building.  2. Fans must be controlled by a humidity control (separate or builtin); OR functioning as a component of a whole-house ventilation system.	

•		

No. Date Description

THE USE OF THESE PLANS AND SPECIFICATION SHALL

BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH

THEY WERE PREPARED AND PUBLICATION THEREOF

SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE

CONTACT WITH THESE PLANS AND SPECIFICATIONS

Mr. and Mrs. Alon

2256 DEODARA DR.

LOS ALTOS, CA

Mr. and Mrs. Alon

2256 DEODARA DR.

LOS ALTOS, CA

SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE

PLANS AND SPECIFICATIONS REMAINS WITH

ACCEPTANCE OF THE RESTRICTIONS.

Client:

Project:

KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL

4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

ate:	12-07-

FK

Scale: N.T.S

Drawn By:


Job No: 2020.11

Signature:

Sheet Title:

CALGreen **MANDATORY MEASURES** 

Sheet No.:



No. Date Description


BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/8"=1'-0"

Drawn By: FK


Job No: 2020.11

Signature:

Sheet Title:

EXISTING SITE PLAN

Sheet No.:



No. Date Description


BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/8"=1'-0"

Drawn By: FK


2020.11

Signature:

Job No:


Sheet Title :
PROPOSED
SITE PLAN

Sheet No.:




## (E) FIRST FLOOR (INCLUDING GARAGE)

(E) GARAGE	DIMENSIONS	AREA	SQ. FT.
G1	15'-1" x 20'-10"	313.6	SQ. FT.
G2	(5'-4" x 4'-8") /2	12.4	SQ. FT.
G3	3'-1" x 2'-5"	7.3	SQ. FT.
G4	6'-9" x 21'-0"	141.75	SQ. FT.
G5	2'-2" x 5'-10"	12.65	-
(E) GARAGE		487.5	SQ. FT.
EXEMPT	DIMENSIONS	AREA	SQ. FT.
E1	(7'-0" x 6'-0") / 2	21.00	SQ. FT.
(E) FIRST FLOOR	DIMENSIONS	AREA	SQ. FT.
F1	27'-2" x 5'-10"	158.5	SQ. FT.
F2	12'-4" x 8'-0"	98.66	SQ. FT.
F3	41'-8" x 21'-0"	875.00	SQ. FT.
F4	6'-9" x 5'-10"	39.40	SQ. FT.
F5	6'-8" x 6'-0	40.00	SQ. FT.
F6	3'-1" x 2'-4"	7.00	SQ. FT.
F7	$\frac{(3'-1"+1'-6")}{2} \times 1'-4"$	3.1	SQ. FT.
(E) FIRST FLOOR		1,221.66	SQ. FT.



## (E) SHED TO BE REMOVED

SECOND FLOOR	DIMENSIONS	AREA	SQ. FT.
M1	12'-2" x 10'-2"	123	SQ. FT.



## (E) SECOND FLOOR


SECOND FLOOR	DIMENSIONS	AREA	SQ. FT.
S1	24'-9" x 28'-3"	699.00	SQ. FT.
SUB TOTAL AREA		699.00	SQ. FT.

## (E) F.A.R

(E) FIRST FLOOR (INCLD. GARAGE) (E) SECOND FLOOR	1709.16 669.00	SQ. FT.
TOTAL F.A.R	2,378.16	SQ. FT.

## (E) LOT COVERAGE

(E) FIRST FLOOR (INCLD. GARAGE) (E) SHED	1709.16 123	SQ. FT
TOTAL LOT COVERAGE	1,832.16	SQ. FT




BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

 Date:
 12-07-20

 Scale:
 1/8"=1'-0"

 Drawn By:
 FK


Job No: 2020.11


Signature:

Sheet Title:

EXISTING AREA
CALCULATION
DIAGRAM

Sheet No.:





## (N) FIRST FLOOR (INCLUDING GARAGE)

(N) FIRST FLOOR	DIMENSIONS	AREA	SQ. FT.
F0	EXISTING (SEE SHT. A-1.1)	1709.16	SQ. FT.
F1	6'-6" x 28'-8"	186.3	SQ. FT.
F2	10'-4" x 2'-0"	20.66	SQ. FT.
F3	33'-11 x 6'-6"	220.78	SQ. FT.
F4	(23'-4" x 12'-4") / 2	143.38	SQ. FT.
F5	(7'-3" x 6'-6") / 2	23.5	SQ. FT.
F6	0'-2" x 1'-10"	0.3	SQ. FT.
F7 (This area is demolitio	n) 12'-4" x 0'-4"	-4.1	SQ. FT.
(N) FIRST FLOOR		2,299.98	SQ. FT.

(N) BASEMENT	DIMENSIONS	AREA	SQ. FT.	
E1	4'-1" x 6'-6"	26.34	SQ. FT.	
E2	(7'-6" x 6'-6") /2	24.2	SQ. FT.	
E3	5'-8" x 6'-1"	34.5	SQ. FT.	
E4	5'-10" x 12'-4"	71.7	SQ. FT.	
E5	(23'-4" x 12'-4") / 2	143.38	SQ. FT.	
E6	15'-6" x 9'-2"	140.89	SQ. FT.	
E7	(7'-0" x 6'-0") / 2	21.00	SQ. FT.	
(N) FIRST FLOOR		462.01	SO FT	•

## (N) SECOND FLOOR

(N) SECOND FLOOR	DIMENSIONS	AREA	SQ. FT.
S0	EXISTING (SEE SHT. A-1.1)	699.00	SQ. FT.
S1	18'-7" x 10'-10"	201.3	SQ. FT.
S2	9'-4" x 11'-10"	110.50	SQ. FT.
S3	15'-10" x 11'-6"	181.68	SQ. FT.
S4	6'-10" x 12'-7"	86.00	SQ. FT.
S5	17'-2" x 17'-7"	301.25	SQ. FT.
(N) SECOND FLOOR		1,579.73	SQ. FT.

## (N) F.A.R

(N) FIRST FLOOR (INCLD. GARAGE) (N) SECOND FLOOR	2299.98 1579.73	SQ. FT. SQ. FT.
TOTAL F.A.R	3,879.71	SQ. FT.

## (N) LOT COVERAGE

N) FIRST FLOOR (INCLD. GARAGE) N) BASEMENT ( FIRST FLOOR WITH DEFINITION OF BAEXEMPT FROM F.A.R BUT NOT FROM LO	2299.98 SEMENT T COVERAGE ) 462.01	SQ. FT. SQ. FT.
TOTAL LOT COVERAGE	2,761.99	SQ. FT.

No. Date Description

\[ \triangle \]
\[ \triangle \]
\[ \triangle \]
\[ \triangle \]


THE USE OF THESE PLANS AND SPECIFICATION SHALL BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/8"=1'-0"

FK

Job No: 2020.11


Signature:


Drawn By:

Sheet Title:

PROPOSED AREA CALCULATION DIAGRAM

Sheet No.:







EXISTING :2256 DEODARA DR.



PROPOSED: 2256 DEODARA DR.




EXISTING:2256 DEODARA DR.
















No. Date Description


THE USE OF THESE PLANS AND SPECIFICATION SHAID BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20

Scale: N.T.S

Drawn By: FK

Job No: 2020.11

Signature:

Sheet Title:
NEIGHBORHOOD
COMPATIBILITY
WORKSHEET

Sheet No.:

NC-1.0



City of Los Altos Planning Division (650) 947-2750 Planning@losaltosca.gov

NEIGHBORHOOD COMPATIBILITY WORKSHEET

In order for your design review application for single-family residential remodel/addition or new construction to be successful, it is important that you consider your property, the neighborhood's special characteristics that surround that property and the compatibility of your proposal with that neighborhood. The purpose is to help you understand your neighborhood before you begin the design process with your architect/designer/builder or begin any formal process with the City of Los Altos. Please note that this worksheet must be submitted with your 1<sup>st</sup> application.

The Residential Design Guidelines encourage neighborhood compatibility without necessarily forsaking individual taste. Various factors contribute to a design that is considered compatible with a surrounding neighborhood. The factors that City officials will be considering in your design could include, but are not limited to: design theme, scale, bulk, size, roof line, lot coverage, slope of lot, setbacks, daylight plane, one or two-story, exterior materials, landscaping et cetera.

It will be helpful to have a site plan to use in conjunction with this worksheet. Your site plan should accurately depict your property boundaries. The best source for this is the legal description in your deed.

Photographs of your property and its relationship to your neighborhood (see below) will be a necessary part of your first submittal. Taking photographs before you start your project will allow you to see and appreciate that your property could be within an area that has a strong neighborhood pattern. The photographs should be taken from across the street with a standard 35mm camera and organized by address, one row for each side of the street. Photographs should also be taken of the properties on either side and behind your property from on your property.

This worksheet/check list is meant to help you as well as to help the City planners and Planning Commission understand your proposal. Reasonable guesses to your answers

	orthood Compatibility Worksheet Page 1 at constitutes your neighborhood" on page 2.
Address Date:	2256 DEODARA Dr. 6/4/2021
8. L	Lot Slope: (Pg. 25 Design Guidelines)
	Does your property have a noticeable slope? Yes
From re	What is the direction of your slope? (relative to the street) ear yard to front yard.
	Is your slope higher lower same in relationship to to neighboring properties? Is there a noticeable difference in grade betwee your property/house and the one across the street or directly behind?
9. L	andscaping:
	Are there any frequently used or typical landscaping features on your str (i.e. big trees, front lawns, sidewalks, curbs, landscape to street edge, etc.

Are there any major existing landscaping features on your property and how is the unimproved public right-of-way developed in front of your

What is the width of the roadway paving on your street in feet? \_\_\_\_\_

Is the shoulder area (unimproved public right-of-way) paved, unpaved,

Is there a parking area on the street or in the shoulder area? Yes

gravel, landscaped, and/or defined with a curb/gutter? \_\_\_\_

The house is visible from street . The project is located on a corner lot.

property (gravel, dirt, asphalt, landscape)?

	2256 DEODARA Dr. 6/4/2021	-	
nat c	onstitutes your neighbo	rhood?	
	s no clear answer to this q		

the purpose of this worksheet, consider first your street, the two contiguous homes on either side of, and directly behind, your property and the five to six homes directly across the street (eight to nine homes). At the minimum, these are the houses that you should photograph. If there is any question in your mind about your neighborhood boundaries, consider a radius of approximately 200 to 300 feet around your property and consider that your neighborhood.

### Streetscape

	一一	
	Lynical heighborhood lot size**	
•	Typical neighborhood lot size*:	

Lot area: 10000 to 1	13000 square fe	eet
Lot dimensions:	Length See NC-1.0	feet
	Width See NC-1.0	feet
If your lot is signifi	icantly different than the	ose in your neighborhood, then
note its: area	, length	, and
width	·	

2. Setback of homes to front property line: (Pgs. 8-11 Design Guidelines)

Existing front setback if home is a remodel? Yes
What % of the front facing walls of the neighborhood homes are at the
front setback 100 %
Existing front setback for house on left 25(+/-) ft./on right
25 (+/-) ft.
Do the front setbacks of adjacent houses line up? Yes

3. Garage Location Pattern: (Pg. 19 Design Guidelines)

Indicate the relationship of garage locations in your neighborhood\* only on your street (count for each type) Garage facing front projecting from front of house face 7 Garage facing front recessed from front of house face 0 Garage in back yard 0 Garage facing the side  $\frac{1}{2}$ Number of 1-car garages 0; 2-car garages 7; 3-car garages 0

Neighborhood Compatibility Worksheet	Page 2
* See "What constitutes your neighborhood", (page 2).	_
Address: 2230 DEODAKA DI.	

11. What characteristics make this neighborhood\* cohesive?

Such as roof material and type (hip, gable, flat), siding (board and batten,
cement plaster, horizontal wood, brick), deep front yard setbacks,
horizontal feel, landscape approach etc.:
Stucco and roof material and form as well as landscape approach

### **General Study**

Date: 6/4/2021

A. Have major visible streetscape changes occurred in your neighborhood? YES NO

B. Do you think that most (~ 80%) of the homes were originally built at the YES INO

C. Do the lots in your neighborhood appear to be the same size? YES INO

D. Do the lot widths appear to be consistent in the neighborhood? YES INO

E. Are the front setbacks of homes on your street consistent (~80% within 5 YES NO

F. Do you have active CCR's in your neighborhood? (p.36 Building Guide) ☐ YES ☒ NO

G. Do the houses appear to be of similar size as viewed from the street? YES NO

H. Does the new exterior remodel or new construction design you are planning relate in most ways to the prevailing style(s) in your existing neighborhood?

×	YES	NO

Address: 2256 DEODARA Dr. Date: 6/4/2021

4. Single or Two-Story Homes:

What % of the homes in your neighborhood\* are: One-story 80 Two-story 20

5. Roof heights and shapes:

Is the overall height of house ridgelines generally the same in your neighborhood\*? Yes Are there mostly hip \_\_\_\_, gable style \_\_\_\_, or other style \_\_\_\_ roofs\*? Do the roof forms appear simple \_\_\_\_\_ or complex \_\_\_\_\_? Do the houses share generally the same eave height Yes ?

6. Exterior Materials: (Pg. 22 Design Guidelines)

What siding materials are frequently used in your neighborhood\*?

<u>✓</u> wood shingle <u>✓</u> stucco <u>\_\_</u> board & batten <u>\_\_</u> clapboard \_\_ tile \_\_ stone <u>v</u> brick <u>v</u> combination of one or more materials (if so, describe) Stucco and wood siding combo

What roofing materials (wood shake/shingle, asphalt shingle, flat tile, rounded tile, cement tile, slate) are consistently (about 80%) used?

If no consistency then explain: Asphalt Shingles and Shingle

7. Architectural Style: (Appendix C, Design Guidelines)

Does your neighborhood\* have a <u>consistent</u> identifiable architectural style? YES INO

Type? Ranch Shingle Tudor Mediterranean/Spanish ☐ Contemporary ☐ Colonial ☐ Bungalow ☐ Other

Neighborhood Compatibility Worksheet
* See "What constitutes your neighborhood" (page 2)

Page 3

Address:	2256 DEODARA Dr.
Date:	6/4/2021

### **Summary Table**

Please use this table to summarize the characteristics of the houses in your immediate neighborhood (two homes on either side, directly behind and the five to six homes directly across the street).

	Address	Front setback	Rear setback	Garage location	One or two stories	Height	Materials	Architecture (simple or complex)
N-1:	2246 DEODARA DR.	25'	25'	FRONT	ONE STORY	17 FEET	WOODSIDE	SIMPLE
N-2:	1574 HONEYSUCKLE PL	25'	25'	FRONT	TWO STORY	20 FEET	STUCCO	SIMPLE
N-3:	1565 HONEYSUCKLE PL.	25'	25'	FRONT	ONE STORY	18 FEET	WOOD SIDING	SIMPLE
N-4:	2255 DEODARA DR.	25'	25'	FRONT	ONE STORY	16 FEET	WOOD SIDING	SIMPLE
N-5:	2265 DEODARA DR.	25'	25'	FRONT	ONE STORY	17 FEET	STUCCO	SIMPLE
N-6:	2275 DEODARA DR.	25'	25'	SIDE	ONE STORY	15 FEET	WOOD SIDING	SIMPLE
N-7:	2285 DEODARA DR.	25'	25'	FRONT	ONE STORY	17 FEET	STUCCO	SIMPLE

Neighborhood Compatibility Worksheet \* See "What constitutes your neighborhood", (page 2).

Page 6

REFER TO SHEET NC-1.0 FOR PICTURES AND SITE PLAN

No. Date	Description
$\overline{\triangle}$	
<u> </u>	
<u> </u>	
	PLANS AND SPECIFICATION SHALL


THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE, REUSE IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date:	12-07-2
Scale:	N.T.C

Job No: 2020.11

FK

Signature:


Drawn By:

Sheet Title: NEIGHBORHOOD COMPATIBILITY WORKSHEET

Sheet No.:

No major landscape.

10. Width of Street:



LEGEND	
	EXISTING WALL TO REMAIN.
	EXISTING WALL TO BE REMOVED.
	ITEMS TO REMAIN.
	ITEMS TO BE REMOVED.

---- NEW FOOT PRINT

No. Date Description

THE USE OF THESE PLANS AND SPECIFICATION SHALL BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH


BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/4"=1'-0"

Drawn By: FK


Job No: 2020.11

Signature:

Sheet Title:

EXISTING FIRST FLOOR PLAN / DEMO PLAN

Sheet No.:



EXISTING SECOND FLOOR PLAN / DEMO PLAN

LEGEND	
	EXISTING WALL TO REMAIN.
	EXISTING WALL TO BE REMOVED.
	ITEMS TO REMAIN.
	ITEMS TO BE REMOVED.

No. Date	Description
$\overline{\bigwedge}$	


THE USE OF THESE PLANS AND SPECIFICATION SHALL BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/4"=1'-0"

FK

Job No: 2020.11


Signature:

Drawn By:

Sheet Title:


EXISTING SECOND FLOOR PLAN / DEMO PLAN

Sheet No.:



PROPOSED FIRST FLOOR PLAN





DETAIL REFRENCE

Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

No. Date Description

THEY WERE PREPARED AND PUBLICATION THEREOF


IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE

Mr. and Mrs. Alon

2256 DEODARA DR.

LOS ALTOS, CA

ACCEPTANCE OF THE RESTRICTIONS.



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/4"=1'-0"

Drawn By: FK


Job No: 2020.11


Signature:

Sheet Title:

PROPOSED FIRST FLOOR

Sheet No.:





No. Date Description

\[ \int \]


THE USE OF THESE PLANS AND SPECIFICATION SHALL BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/4"=1'-0"

Drawn By: FK


Job No: 2020.11

Signature:

Sheet Title:

PROPOSED SECOND FLOOR

Sheet No.:



## EXISTING ROOF PLAN / DEMO PLAN



LEGEND	
	EXISTING ROOF TO BE DEMOLISHED
	EXISTING ROOF TO REMAIN
[]	FOOTPRINT OF EXISTING BUILDING

No. Date	Description
$\triangle$	
<u> </u>	
<u> </u>	
THE USE OF THESE I	PLANS AND SPECIFICATION SHALL


THE USE OF THESE PLANS AND SPECIFICATION SHALL BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/4"=1'-0"

Drawn By: FK

2020.11

Signature:


Job No:

Sheet Title:

EXISTING ROOF PLAN PLAN / DEMO PLAN

Sheet No.:

A-3.0



PROPOSED ROOF PLAN

LEGEND	
	EXISTING ROOF TO REMAIN
	NEW ROOF

FOOTPRINT OF EXISTING BUILDING


THE USE OF THESE PLANS AND SPECIFICATION SHALL BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/4"=1'-0"

Drawn By: FK

Job No: 2020.11

Signature:


Sheet Title:

PROPOSED ROOF PLAN

Sheet No.:

A-3.1





EXISTING FRONT ELEVATION

No. Date Description


THE USE OF THESE PLANS AND SPECIFICATION SHALL BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

 Date:
 12-07-20

 Scale:
 1/4"=1'-0"

 Drawn By:
 FK


Job No: 2020.11


Signature:

Sheet Title:

EXTERIOR ELEVATION

Sheet No.:





EXISTING RIGHT SIDE ELEVATION

No. Date Description


BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/4"=1'-0"

FK

Drawn By:


Job No: 2020.11

Signature:

Sheet Title:

EXTERIOR ELEVATION

Sheet No.:



No. Date Description


BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

 Date:
 12-07-20

 Scale:
 1/4"=1'-0"

 Drawn By:
 FK


Job No: 2020.11


Signature:

Sheet Title:

EXTERIOR ELEVATION

Sheet No.:





EXISTING LEFT SIDE ELEVATION

No. Date Description


BE RESTRICTED TO THE SPECIFIC SITE FOR WHICH THEY WERE PREPARED AND PUBLICATION THEREOF SHALL BE EXPRESSLY LIMITED TO SUCH USE. REUSE, REPRODUCTION OR PUBLICATION BY ANY METHOD, IN WHOLE OR IN PART, IS PROHIBITED; TITLE TO THE PLANS AND SPECIFICATIONS REMAINS WITH KHADIV-DESIGN. WITHOUT PREJUDICE VISUAL CONTACT WITH THESE PLANS AND SPECIFICATIONS SHALL INSTITUTE PRIMA FACIE EVIDENCE OF THE ACCEPTANCE OF THE RESTRICTIONS.

## Client:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA

## Project:

Mr. and Mrs. Alon 2256 DEODARA DR. LOS ALTOS, CA



4657 TAMPICO WAY SAN JOSE, CA. 95118 Phone (408) 888-6662 farnaz@khadivdesign.com

## KHADIV-DESIGN

Date: 12-07-20 Scale: 1/4"=1'-0"

FK

Job No: 2020.11


Signature:

Drawn By:

Sheet Title:

EXTERIOR ELEVATION


Sheet No.:



CITY APPR

MANAGER: DSK

CALIFORNIA



1sterlingconsultants@gmail.com PHONE: 510.344.8955

NO. BY DATE

MANAGER: DSK

REVISIONS

CITY APPE

CITY OF LOS ALTOS

SANTA CLARA COUNTY

PRINTED: MAY 27, 2021

2020-475

CALIFORNIA